

AMENDMENTS TO THE CLAIMS

The listing of claims below replace all prior versions, and listings, of claims:

- 1           1.       (Currently Amended) A system comprising:  
2                   a memory bus; and  
3                   a plurality of memory controllers, each memory controller to generate  
4 memory requests on the memory bus according to a predetermined priority scheme, the  
5 predetermined priority scheme defining time slots, wherein the memory controllers are  
6 allocated to respective time slots according to the predetermined priority scheme,  
7                   at least two of the plurality of memory controllers adapted to generate  
8 concurrently pending memory requests on the memory bus in plural respective time slots.
- 1           2.       (Cancelled)
- 1           3.       (Cancelled)
- 1           4.       (Original) The system of claim 1, wherein the memory bus comprises a  
2 Rambus channel.
- 1           5.       (Original) The system of claim 1, wherein each memory controller  
2 generates a memory request during a different predetermined time slot.
- 1           6.       (Original) The system of claim 1, wherein the memory bus comprises  
2 plural control portions, each of the control portions associated with corresponding time  
3 slot priority schemes.
- 1           7.       (Original) The system of claim 6, wherein the time slot priority schemes  
2 are staggered.

1           8.       (Original) The system of claim 6, wherein the control portion comprise a  
2 row portion and a column portion.

1           9.       (Original) The system of claim 1, wherein the memory bus comprises  
2 plural portions, each portion associated with a set of memory devices.

1           10.      (Currently Amended) A system comprising:  
2                    a plurality of memory buses ~~bus~~; and  
3                    a hub connected to the plurality of memory buses; and  
4                    a plurality of memory controllers connected to a first one of the memory  
5 ~~bus~~ buses, each memory controller to monitor memory requests generated by another  
6 memory controller in performing memory-related actions,  
7                    the memory controllers to access a second one of the memory buses  
8 through the hub.

1           11.      (Original) The system of claim 10, wherein the memory-related actions  
2 comprise a read-modify-write transaction.

1           12.      (Original) The system of claim 10, wherein the memory-related actions  
2 comprise a cache coherency action.

1           13.      (Original) The system of claim 10, wherein the memory-related actions  
2 comprise a memory request.

1           14.      (Currently Amended) The system of claim 10, ~~the~~ each memory controller  
2 to determine if the memory buses are ~~bus is~~ available based on outstanding requests from  
3 other memory controllers.

1           15.     (Currently Amended) A method for use in a system having plural memory  
2 buses, a hub connected to the memory buses, and a plurality of memory controllers, the  
3 method comprising:

4                   ~~providing multiple memory controllers on a memory bus;~~  
5                   generating requests, by the memory controllers, on the memory ~~bus~~ buses;

6 and

7                   each memory controller monitoring memory-related actions on the  
8 memory buses connected by the hub by at least another memory controller.

1           16.     (Original) The method of claim 15, wherein generating the requests  
2 comprises generating Rambus command packets.

1           17.     (Original) The method of claim 15, wherein generating the requests  
2 comprises the memory controllers generating the requests one at a time according to a  
3 predetermined priority scheme.

1           18.     (Original) The method of claim 17, wherein generating the requests  
2 comprises generating the requests according to a time slot priority scheme.

1           19.     (Original) The method of claim 17, wherein generating the requests  
2 comprises generating the requests according to a request-select priority scheme.

1           20.     (Previously Presented) The method of claim 15, further comprising each  
2 memory controller determining when to generate a memory request based on the  
3 monitoring.

1           21.     (Previously Presented) The method of claim 15, further comprising each  
2 memory controller determining if a lock has been asserted due to presence of a read-  
3 modify-write transaction.

1           22.     (Previously Presented) The method of claim 15, further comprising each  
2 memory controller performing a cache coherency action based on the monitoring.

1           23.     (Currently Amended) An article comprising one or more storage media  
2 containing instructions that when executed cause a memory controller to:  
3                   monitor memory requests from another memory controller on a memory  
4 bus;  
5                   ~~determining~~ determine if a memory request can be generated on the  
6 memory bus based on the monitoring; and  
7                   generate memory requests on the memory bus according to a time slot  
8 priority scheme that defines time slots allocated to respective memory controllers.

1           24.     (Previously Presented) The system of claim 1, wherein the plurality of  
2 memory controllers are connected to the memory bus.

1           25.     (Previously Presented) The system of claim 1, wherein one of the at least  
2 two memory controllers is adapted to generate its memory request on the memory bus  
3 before data is returned for the memory request of the other one of the at least two  
4 memory controllers.

1           26.     (Currently Amended) The system of claim 10, wherein at least two of the  
2 memory controllers are adapted to generate concurrently pending memory requests on the  
3 first memory bus, each of the concurrently pending memory requests comprising control  
4 information and memory address information.

1           27.     (Currently Amended) The system of claim 26, wherein one of the at least  
2 two memory controllers is adapted to generate its memory request including control  
3 information and memory address information on the memory bus before data is returned  
4 for the memory request of the other one of the at least two memory controllers.

1           28.     (Currently Amended) The method of claim 15, wherein generating the  
2 requests on the memory bus comprises at least two of the memory controllers generating  
3 concurrently pending requests on the memory bus, each of the concurrently pending  
4 requests comprising control information and memory address information.

1           29.     (Currently Amended) The method of claim 28, wherein generating  
2 concurrently pending requests comprises one of the at least two memory controllers  
3 generating its request including control information and memory address information on  
4 the memory bus before data is returned for the request of the other of the at least two  
5 memory controllers.

1           30.     (Previously Presented) The article of claim 23, wherein the memory  
2 controllers are connected to the memory bus.

1           31.     (New) The system of claim 1, wherein the predetermined priority scheme  
2 enables the memory controllers to gain access to the memory bus without having to assert  
3 arbitration requests.

1           32.     (New) The system of claim 1, wherein the memory controllers are adapted  
2 to access the memory bus according to a round-robin priority scheme.

1           33.     (New) The system of claim 1, wherein the memory bus comprises a first  
2 memory bus, the system further comprising:

3                   a hub connected to the first memory bus; and

4                   a second memory bus connected to the hub, at least two of the memory  
5 controllers adapted to generate concurrently pending memory requests on the second  
6 memory bus through the hub.

1           34.     (New) The system of claim 33, wherein each of the memory requests  
2 comprises control information and memory address information, the at least two memory  
3 controllers adapted to generate concurrently pending memory requests on the second

4 memory bus by providing control information and memory address information of the  
5 concurrently pending memory requests on the second memory bus.

1 35. (New) The system of claim 33, wherein each of the memory requests  
2 comprises control information and memory address information, the at least two memory  
3 controllers adapted to generate concurrently pending memory requests on the first  
4 memory bus by providing control information and memory address information of the  
5 concurrently pending memory requests on the first memory bus.

1 36. (New) The system of claim 10, wherein the plurality of memory  
2 controllers are each adapted to generate memory requests on the first one of the memory  
3 buses, each memory controller to monitor memory requests on the first one of the  
4 memory buses generated by another memory controller on the first one of the memory  
5 buses.

1 37. (New) The system of claim 10, wherein the plurality of memory  
2 controllers are each adapted to generate memory requests on the second one of the  
3 memory buses, each memory controller to monitor memory requests on the second one of  
4 the memory buses generated by another memory controller on the second one of the  
5 memory buses.

1 38. (New) The system of claim 37, wherein the memory controllers are  
2 adapted to access any of the memory buses according to a time slot priority scheme that  
3 defines a plurality of time slots allocated to respective memory controllers.

1 39. (New) The system of claim 38, wherein the memory controllers are  
2 adapted to access any of the memory buses according to the time slot priority scheme  
3 without asserting arbitration requests.

1           40.   (New) The system of claim 10, further comprising memory devices  
2 connected to respective memory buses, the memory devices accessible by the memory  
3 controllers.

1           41.   (New) The system of claim 11, wherein a first one of the memory  
2 controllers is adapted to generate the read-modify-write transaction, the first one of the  
3 memory controllers to assert a lock indication for a memory location accessed by the  
4 read-modify-write transaction to prevent another one of the memory controllers from  
5 accessing the memory location.

1           42.   (New) The method of claim 15, further comprising:  
2                   the plurality of memory controllers generating memory requests on a first  
3 one of the memory buses; and  
4                   each memory controller monitoring memory requests on the first one of  
5 the memory buses generated by another memory controller on the first one of the  
6 memory buses.

1           43.   (New) The method of claim 15, further comprising:  
2                   the plurality of memory controllers generating memory requests on a  
3 second one of the memory buses through the hub; and  
4                   each memory controller monitoring memory requests on the second one of  
5 the memory buses generated by another memory controller on the second one of the  
6 memory buses.

1           44.   (New) The article of claim 23, wherein generating memory requests on the  
2 memory bus according to the time slot priority scheme is performed without generating  
3 arbitration requests.

---